

POSTMARK AP1170

The AP1170 is an all in one solution for the 1170 printhead. With it's integrated friction feeder, adjustable receiving tray, and vacuum conveyor you can have an "All Purpose" solution for printing. The AP1170 also features a cantilevered design allowing for larger media to be fed under the printhead when the 20" feed width isn't quite enough. Simply remove the feeder (no tools required and feed on larger media such as boxes.



POSTMARK CP1170

The CP1170 is our more industrial solution which includes an industrial 18" x 60" conveyor as well as an innovative cantilevered design to allow larger media to be fed under the printhead. The printhead can also be adjusted (with tools) up to 8" above the belt for feeding directly on erected cartons or other thick materials. Postmark's MPF feeders or Vacuum feeders can also be paired with the CP1170 for an industrial solution for printing on corrugated or other porous materials



POSTMARK TK1170

The TK1170 is our Turnkey kit made for adding the 1170 printhead to existing equipment. The TK1170 comes with everything you need including a custom bridge made to any width, an encoder, and a photocell. The bridge design allows the printhead to move across the conveyor system for easy adjustment. With the 1170's integrated lower paper guide the printhead is protected from substrates and makes sure that substrates are held down during printing.

Versatilitv

Prints on a wide range of porous media types

Permanence

HP pigment ink provides durability in fade, scratch, and water resistance

Photo quality

The four-color ink system produces long-lasting, brilliant colors

Printhead Specifications

Printhead HP PageWide technology TIJ4 printhead, replaceable as part of BnB **Print Swath** 297 mm (11.7 in) Nozzle Count 59136 (4224 x 14) Resolution 1200 nozzles per inch, per color Speed Up to 18ips - 27m/min - 98ft/min Drop Volume 10 pl K, 8.5 pl CMY Ink cartridge type Individual ink supply **HP ink type** Pigmented aqueous ink Ink fill (ml) Approximately 498 black, 237 cyan, 233 magenta, 225 yellow

Operating Conditions

Operating temperature range: 15°C to 30°C (59°F to 86°F) Operating humidity range: 15% to 80% RH (non-condensing), 20% to 80% recommended Storage temperature range: -40°C to 60°C (-40°F to 140°F) Non-operating humidity range: 10% to 90% (non-condensing)



Software Specifications

Connection Ethernet **Driver** Windows (static data only) **Rip Options** Maestro (Xitron Navigator) User Interface 10.1" Touchscreen and Driver/Rip Touch Interface Features Electronic Height Adjust, Cost Calculator



Spot Color Matching Full PDF Support Fastest Professional Grade Rip Global or Specific Color Adjustment POSTMARK Economical - Low Cost Of ownership





POSTMARK SA1170

The SA1170 is the printhead used on the AP1170, CP1170, and TK1170 but in a standalone configuration. It features a 10.1" integrated touchscreen for controlling the printheads electronic height adjustment, cleaning cycles, and network options. It also features relay outputs that can start / stop feeders and conveyors when printing is ready to go. The SA1170 has four mounting pins that can be used for custom applications where the TK1170 isn't the right fit.

Proven reliability

HP's worldwide recognition for product guality, reliability, and service

Ease-of-use

Simple, quick replacement minimizes downtime

POSTMARK INC

FAX 805.594.1455 3197 DUNCAN LANE #A

POSTMARK

PHONE 805.594.1454

SAN LUIS OBISPO, CA 93401

WWW.POSTMARK-USA.COM

UNITED STATES OF AMERICA

Economical output

Efficient ink delivery system provides a low cost-per-print advantage

Cleaning Cycles, Relay output



POSTMARK APS PHONE +45 65 910190

> ENIGHEDSVEJ 21 5000 ODENSE C DENMARK

WWW.POSTMARK.DK

Print Samples Actual Size

No. 10 Window

Ink Cost Per Piece \$0.019



No. 10 Linen

Ink Cost Per Piece \$0.038



Bar Coaster

Ink Cost Per Piece \$0.023

